

CORRIGENDUM/ADDENDUM-1

26.12.2019

NIT No: WAP/ENVT/CSEZ/H-3082/2019/55 Dt.12.12.2019

Title: Civil Works for Construction of Sports Court Facility in SDF-17 Building In Cochin Special Economic Zone

Sl. No	Event	As per NIT	Revised as follows
1	Sl No.10 of Page No.4 of Technical Bid: Last date & time for online submission of Technical & Financial Bid.	26.12.2019 up to 13:00 hours	10.01.2020 up to 13:00 hours
2	Sl No.11 of Page No.4 of Technical Bid: Offline Submission of Tender Fees, EMD etc. as detail in Tender	26.12.2019 up to 15:00 hours	10.01.2020 up to 15:00 hours
3	Sl No.12 of Page No.4 of Technical Bid: Online opening of Technical Bid	26.12.2019 at 15:30 hours	10.01.2020 at 15:30 hours
4	BILL OF QUANTITIES (BOQ): Page No.131 of Financial Bid: BOQ Sl. No. 10	Providing and applying integral crystalline (dry shake) of hydrophilic in nature for waterproofing treatment to the RCC structures like basement raft, foundation slab, sewage & water treatment plant slab, warehouses floor, parking structures and water tank base slab etc. sprinkled @0.60kg per sqm or higher as recommended by the manufacturer's specification over the lean concrete of above cited structures. The material shall meet the requirements as specified in ACI-212-3R-2010 i.e. by reducing permeability of concrete by more than 85%, compared control concrete as per DIN 1048 and resistant to 16 bar hydrostatic pressure on negative side. The crystalline dryshake shall be capable of self-healing of cracks up to a width of 0.50mm. The work shall be carried out all complete as per specification and the direction of the Engineer-in-charge. The product performance shall carry guarantee for 10 years against any leakage.	a) Providing and applying integral crystalline (dry shake) of hydrophilic in nature for waterproofing treatment to the RCC structures like basement raft, foundation slab, sewage & water treatment plant slab, warehouses floor, parking structures and water tank base slab etc. sprinkled @0.60kg per sqm or higher as recommended by the manufacturer's specification over the lean concrete of above cited structures. The material shall meet the requirements as specified in ACI-212-3R-2010 i.e. by reducing permeability of concrete by more than 85%, compared control concrete as per DIN 1048 and resistant to 16 bar hydrostatic pressure on negative side. The crystalline dryshake shall be capable of self-healing of cracks up to a width of 0.50mm. The work shall be carried out all complete as per specification and the direction of the Engineer-in-charge. The product

Sl. No	Event	As per NIT	Revised as follows
			<p>performance shall carry guarantee for 10 years against any leakage.</p> <p>b) Post Construction Antiter- Mite Treatment to entire floor area by drilling holes of 12mm dia at 300mm intervals both ways and injecting chemical till refusal or maximum 1 litre / hole till the soil underneath soaks using the Chemicals like Chloropyripos emulsifiable (IS 8944-1978) E.C 20% with 1% concentration mixed with water in 1:19 ratio (i.e., 1 litre of Chemical to 19 litres of water). The holes are to be plugged with CM 1:2 (1 cement: 2 coarse sand) to match with the existing floor.</p>
5	<p>BILL OF QUANTITIES (BOQ): Page No.133 of Financial Bid: BOQ Sl. No 22</p>	<p>9 Layers Acrylic Water Based Hybride Cushion Out Door Sports Flooring With PU Top Coating. . Supply and apply of Acrylic cushion sports flooring having one coat of water based PU primer, One coat of Acrylic Resurfacer, Three Layers of Premium Acrylic Rubber Cushion, One Layer of Pre - Base colour coating, Two Coats of HPU Top coat and Line Marking. Line Marking for Four courts - Badminton, Basket ball and Volley Ball. Applied on concrete surface after cleaning of surface and removing all dust and lose particles from the surface.</p>	<p>Providing and laying of International Tennis Federation (ITF) or The International Basketball Federation (FIBA) or The Federation Internationale de Volleyball (FIVB) or any other international federation approved 09 layers Acrylic cushioned surface system over an already prepared concrete base suitable for Basketball, Volleyball, Badminton and Table Tennis with all line markings manufactured in Europe or United States of America with all line markings complete.</p>
6	BOQ Sl. No 23	Indoor Cricket Flooring as per Specifications	<p>Providing and laying a 9 layer 5mm Acrylic cushioned surface system over an already prepared concrete base suitable specially for Cricket with all line markings complete manufactured in Europe or United States of America comprising of a 4mm High density shock pad glued to the concrete surface with a special adhesive sealed with 2 layers of sealer coats, 2 layers of a Ty coat, 2 layers of filler coats and 2 Top coats that will also include all Line Markings.</p>

Special Condition:

1. Flooring - max 5 years warranty should be issued by the contractor.
2. Flooring should be approved either by
 - a. International Tennis Federation(ITF)
 - b. International Basketball Federation (FIBA)
 - c. Federation International Volleyball (FIVB)
 - d. Or any other international federation.
3. **Rate Quoted in the BOQ shall consider the change in specification mentioned in this corrigendum/addendum.**

For and on behalf of WAPCOS LIMITED

**General Manager (SEZ)
WAPCOS Limited,
CSEZ Project Office**